

APE

MANUFACTURING

CEILING LIGHT GUARD

Product code: APE CLGMkII

PRODUCT ADVANTAGES

- Easy to install.
- Can be surrounded by insulation.
- Can be fitted hard up against timber and metal ceiling joists.
- Rodent-proof, fully-vented top.
- Optional transformer/driver pocket.
- Helps prevent roof fires.

TECHNICAL SPECIFICATIONS

Product code	APE CLGMkII
Colour	White
Material	Flame-retardant Nylon
Dimensions	Height: 225mm Diameter: 140mm
Minimum order	10
Carton quantity	50

Tested to AS/NZS 5110:2011

INSTALLATION INSTRUCTIONS

- Install Low Voltage, R80 and LED down lights according to the manufacturer's instructions. Place the APE Ceiling Light Guard centrally over the Down Light.
- If the light tail is to run under the guard remove a small portion of the appropriate cut-out ensuring opening is ONLY as large as needed to accommodate the spring clips and cable. Check that light tail does not make contact with the light fitting.
- If tail is to run through the side opening into the side pocket, ensure cables cannot slip back down onto the light fitting.
- Ensure there is no debris between the guard and ceiling.
- Fix guard to ceiling by applying heat resistant adhesive or silicon on the tabs. If the ceiling is uneven sealant may be required to fill gaps.
- Insulation can be installed hard against the CLG MKII.
- CLG MKII can be installed hard against timber joists.

OPTIONAL Transformer/Driver Pocket

- Attach transformer/driver pocket to the side of the APE Ceiling Light Guard by pushing firmly.
- Push tail through the perforated circular cut out and connect to light fitting, then place the transformer/driver into the pocket. If tail is to run through the side opening into the side pocket, ensure cables cannot slip back down onto the light fitting.
- If the light tail is to run under the guard, remove a small portion of the appropriate cut-out ensuring opening is ONLY as large as needed to accommodate the spring clips and cable, place the transformer/driver in the pocket. Check that tail is not in contact with the light fitting.



Product code	APECLG-P
Colour	White
Material	Flame-retardant Nylon
Dimensions	Height: 70mm Width: 55mm Depth: 48mm
Minimum order	25
Carton quantity	25/250

APE Manufacturing
Unit 3, 27 Darlot Road, LANDSDALE, WA 6065
PO BOX 1235, WANGARA, WA 6947

Ph: (08) 6305 0681
Fax: (08) 6305 0633
Email: sales@apemanufacturing.com.au